



Model	GTJZ0608S
<b>PRODUCTIVITY</b>	
Max. platform height	5.80 M
Max. working height	7.80 M
Extension outreach	0.90 M
Turning radius (outside)	1.49 M
Turning radius (inside)	0.04 M
Rising / falling speed (without loading)	15-20 s / 25-30 s
Grade ability	25 %
Load Capacity (platform)	230 kg
Driving speed (stowed)	0~4 km/h
Driving speed (raised)	0~0.8km/h
Max allowable wind speed indoor	0 m/s
Max allowable wind speed outdoor	-
Max allowable slope (front/back)	3 °
Max allowable slope (side/side)	1.5 °
Max platform occupants indoor	2 p
Max platform occupants outdoor	-
Max allowable side force indoor	400 N
Max allowable side force outdoor	-
<b>DIMENSIONS</b>	
Overall length (stowed)	1.78 m
Overall width (stowed)	0.76 m
Overall height (stowed, guardrail folded)	-
Overall height (stowed, guardrail unfolded)	2.11 m
Ground clearance	0.07 m
Wheelbase	1.315 m
Platform size (L x W x H)	1.64 x 0.76 x 1.10 m
Overall weight	1328 kg
Tire	305 x 115 mm / solid
Hydraulic oil tank vol.	16 l
Hydraulic system vol.	18 l
Battery	6V*4/225 AH
Control voltage	24 VDC
Power unit	24 VDC, 3 KW
Drive & steer model	2 WD, front wheel
Input voltage of charger	100~240V AC
Output current of charger	25 A
Hydraulic system pressure	24 MPA
Brake	2 rear wheel

## VDS. NV

NIEUWE STEENWEG 25 - 9810 EKE-NAZARETH  
TEL 09 385 37 45 - FAX 09 385 37 44

INFO@NVVDS.BE  
WWW.NVVDS.BE

BTW BE 0449.061.401  
RPR OUDENAARDE

KBCIBAN BE08447061206113  
BIC KREDBEBB

