



Model	GTJZ0608 / GN 2032
PRODUCTIVITY	
Max. platform height	6.30 M
Max. working height	8.30 M
Extension outreach	0.90 M
Turning radius (outside)	2.10 M
Turning radius (inside)	0 M
Rising / falling speed (without loading)	25-30 s / 30-35 s
Grade ability	30 %
Load Capacity (platform)	380 kg
Driving speed (stowed)	0~3.20 km/h
Driving speed (raised)	0~0.8km/h
Max allowable wind speed indoor	0 m/s
Max allowable wind speed outdoor	12.5 m/s
Max allowable slope (front/back)	3 °
Max allowable slope (side/side)	1.5 °
Max platform occupants indoor	2 p
Max platform occupants outdoor	1 p
Max allowable side force indoor	400 N
Max allowable side force outdoor	200 N
DIMENSIONS	
Overall length (stowed)	2.39 m
Overall width (stowed)	0.81 m
Overall height (stowed, guardrail folded)	1.83 m
Overall height (stowed, guardrail unfolded)	2.22 m
Ground clearance	0.10 m
Wheelbase	1.85 m
Platform size (L x W x H)	2.25 x 0.81 x 1.10 m
Overall weight	1770 kg
Tire	380 x 125 mm / solid
Hydraulic oil tank vol.	14 l
Hydraulic system vol.	18 l
Battery	6V*4/225 AH
Control voltage	24 VDC
Power unit	24 VDC, 3 KW
Drive & steer model	2 WD, front wheel
Input voltage of charger	100~240V AC
Output current of charger	25 A
Hydraulic system pressure	24 MPA
Brake	2 rear wheel

VDS. NV

NIEUWE STEENWEG 25 - 9810 EKE-NAZARETH
TEL 09 385 37 45 - FAX 09 385 37 44

INFO@NVVDS.BE
WWW.NVVDS.BE

BTW BE 0449.061.401
RPR OUDENAARDE

KBCIBAN BE08447061206113
BIC KREDBEBB

