



| Model                                        | GTJZ0812 / GN 2646   |
|----------------------------------------------|----------------------|
| <b>PRODUCTIVITY</b>                          |                      |
| Max. platform height                         | 8.10 M               |
| Max. working height                          | 10.10 M              |
| Extension outreach platform / total outreach | 0.90 m / 1.47 m      |
| Turning radius (outside)                     | 2.35 M               |
| Turning radius (inside)                      | 0 M                  |
| Rising / falling speed (without loading)     | 30-35 s / 35-40 s    |
| Grade ability                                | 25 %                 |
| Load Capacity (platform)                     | 450 kg               |
| Driving speed (stowed)                       | 0~3.20 km/h          |
| Driving speed (raised)                       | 0~0.8km/h            |
| Max allowable wind speed indoor              | 0 m/s                |
| Max allowable wind speed outdoor             | 12.5 m/s             |
| Max allowable slope (front/back)             | 3 °                  |
| Max allowable slope (side/side)              | 1.5 °                |
| Max platform occupants indoor                | 2 p                  |
| Max platform occupants outdoor               | 2 p                  |
| Max allowable side force (indoor)            | 400 N                |
| Max allowable side force (outdoor)           | 400 N                |
| <b>DIMENSIONS</b>                            |                      |
| Overall length (stowed)                      | 2.39 m               |
| Overall width (stowed)                       | 1.15 m               |
| Overall height (stowed, guardrail folded)    | 1.96 m               |
| Overall height (stowed, guardrail unfolded)  | 2.35 m               |
| Ground clearance                             | 0.10 m               |
| Wheelbase                                    | 1.85 m               |
| Platform size (L x W x H)                    | 2.25 x 1.15 x 1.10 m |
| Overall weight                               | 2490 kg              |
| Tire                                         | 380 x 125 mm / solid |
| Hydraulic oil tank vol.                      | 14 l                 |
| Hydraulic system vol.                        | 18 l                 |
| Battery                                      | 6V*4/225 AH          |
| Control voltage                              | 24 VDC               |
| Power unit                                   | 24 VDC, 3 KW         |
| Drive & steer model                          | 2 WD, front wheel    |
| Input voltage of charger                     | 100~240V AC          |
| Output current of charger                    | 25 A                 |
| Hydraulic system pressure                    | 24 MPA               |
| Brake                                        | 2 rear wheel         |

## VDS. NV

NIEUWE STEENWEG 25 - 9810 EKE-NAZARETH  
TEL 09 385 37 45 - FAX 09 385 37 44

INFO@NVVDS.BE  
WWW.NVVDS.BE

BTW BE 0449.061.401  
RPR OUDENAARDE

KBCIBAN BE08447061206113  
BIC KREDBEBB

